

Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Not for sale in the USA

Section 1. IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

1.1 Product identifier

Trade name Solid STRIKE 110 MSS and Solid STRIKE 115 MSS Carbon Steel Covered Electrodes

Article-Nº

| Product/Article | Diameter | Packaging | Part |
|--|------------|-----------|----------|
| | (mm/lnch) | (kg) | Number |
| Solid STRIKE 110 Electrode E6010IP | 4.0 | 20 | 11023636 |
| Solid STRIKE 110 Electrode E6010IP | 5.0 | 20 | 11023637 |
| Solid STRIKE 110 Electrode E6011 | 2.4 | 16 | 11023638 |
| Solid STRIKE 110 Electrode E6011 | 3.2 | 20 | 11023639 |
| Solid STRIKE 110 Electrode E6011 | 4.0 | 20 | 11023640 |
| Solid STRIKE 110 Electrode E6013V | 2.4 | 16 | 11023643 |
| Solid STRIKE 110 Electrode E6013V | 3.2 | 20 | 11023644 |
| Solid STRIKE 110 Electrode E7014IP | 2.4 | 16 | 11023645 |
| Solid STRIKE 110 Electrode E7014IP | 3.4 | 20 | 11023646 |
| Solid STRIKE 110 Electrode E7024IP | 3.2 | 20 | 11023665 |
| Solid STRIKE 110 Electrode E7024IP | 4.0 | 20 | 11023666 |
| Solid STRIKE 110 Electrode E7024IP | 5.0 | 20 | 11023667 |
| Solid STRIKE 110 Electrode E7018-1MRP | 2.4 | 16 | 11023668 |
| Solid STRIKE 110 Electrode E7018-1MRP | 3.2 | 20 | 11023669 |
| Solid STRIKE 110 Electrode E7018-1MRP | 4.0 | 20 | 11023670 |
| Solid STRIKE 110 Electrode E7018 MR PLUS | 4.8 | 20 | 11023671 |
| Solid STRIKE 110 Electrode E7018 AC | 2.4 | 16 | 11023682 |
| Solid STRIKE 110 Electrode E7018 AC | 3.2 | 20 | 11023684 |
| Solid STRIKE 110 Electrode 7018AC | 3.2 | 20 | 11023685 |
| Solid STRIKE 110 Electrode E7018AC | 4.0 | 20 | 11023686 |
| Solid STRIKE 110 Electrode 7018AC | 4.0 | 20 | 11023687 |
| Solid STRIKE 110 Electrode 7018 Extra | 2.4 | 16 | 11101709 |
| Solid STRIKE 110 Electrode 7018 Extra | 3.2 | 20 | 11101710 |
| Solid STRIKE 110 Electrode 7018 Extra | 4.0 | 20 | 11101711 |
| Solid STRIKE 110 Electrode 7018 Extra | 4.8 | 20 | 11101712 |
| Solid STRIKE 110 Electrode 7018 Extra | 6.4 | 20 | 11101713 |
| Solid STRIKE 110 Electrode E7017IP | 3.2 | 20 | 11183120 |
| Solid STRIKE 110 Electrode 7018 | 2.4 | 16 | 11183121 |
| Solid STRIKE 110 Electrode E7024IP | 3.2 | 20 | 11183124 |
| Solid STRIKE 110 Electrode 7018 | 3.2 | 20 | 11183122 |
| Solid STRIKE 110 Electrode 7018AC | 3.2 | 20 | 11226918 |
| Solid STRIKE 115 Electrode E7018-1H4R | 2.5 (3/32) | 3.4 | 11312710 |
| Solid STRIKE 115 Electrode E7018-1H4R | 2.5 (3/32) | 4.2 | 11312711 |
| Solid STRIKE115 Electrode E7018-1H4R | 3.2(1/8) | 4.2 | 11312712 |
| Solid STRIKE 115 Electrode E7018-1H4R | 4.0 (5/32) | 4.6 | 11312713 |
| Solid STRIKE 115 Electrode E7018-1H4R | 4.0 (5/32) | 5.8 | 11312714 |
| Solid STRIKE 115 Electrode E7018-1H4R | 5.0 (3/16) | 5.6 | 11312715 |
| Solid STRIKE 115 Electrode E7018-1H4R | 6.0 (1/4) | 5.8 | 11312716 |



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

1.2 Relevant identified uses of the substance or mixture and uses advised against

Article type SMAW Un- and Low-alloyed electrodes Classification: AWS SFA 5.1/5.5 or other

Use Electric arc welding

1.3 Details of the supplier of the safety data sheet

Supplier Messer Canada Inc.

Street address 5860 Chedworth Way, Mississauga

Ontario L5R 0A2

Canada

Telephone 1-866-385-5349

Fax 905-501-1717

Email Info.mg.ca@messer-ca.com

1.4 Emergency telephone number

Available outside office hours Yes

Emergency phone number (24 Hour): (905) 501-0802 or CHEMTREC (800) 424-9300

Other

Additional product information Web site: www.messer-ca.com

Section 2. HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to applicable national regulations.

2.2 Label elements

Refer to label.

2.3 Other hazards

When the product is used in the welding process the most important hazards are:

Overexposure to fumes and gases from welding can be dangerous to health.

Watch out for splatter, hot metal and slag. It may cause skin burn and cause fire.

Arc rays can injure eyes and burn skin. Electric shock can kill. Avoid touching live electrical parts.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Section 3. COMPOSITION / INFORMATION ON INGREDIENTS

3.1 Substances

This product is a mixture and please refer to Section 3.2

3.2 Mixtures

| Miled steel core Fe Mn Cr Ni Cu Si Typical 98-99 <0.6 <0.1 <0.1 <0.1 <0.2 Flux coating Cellulose E6012, E6010, 6011 Rutile Hydrogen E7024 Rutile Fronce Product E7024 Cas No. Limestone and/or Carbonate <0.10 20-30 <10 10-20 1317-65-3 Magnesite (total inhalable dust) (respirable dust) 5-10 <5 - - - 546-93-0 Cellulose (total inhalable dust) (respirable dust) 25-60 <15 - - - 9004-34-6 Iron Oxides (as Fe) <10 <10 <10 <10 > 1309-37-6 Inorganic Fluorides (as Fe) <10 <10 <10 ><10 ><10 ><10 9004-34-6 Inorganic Enurides (as Fe) <10 10-30 <10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 ><10 | 3.2 Mixtures | | | | | | |
|---|-------------------------|---------------------|--------|--------------------|----------------|----------------|------------|
| Flux coating | Mild steel core | Fe | Mn | Cr | Ni | Cu | Si |
| Flux coating Cellulose E6010, 6011 Rutine E6012, 6013 Hydrogen E7016, 7018 Iron Powder E7024 Prowder E7028 Cas No. Limestone and/or Calcium Carbonate - <10 | Typical | 98-99 | <0.6 | <0.1 | <0.1 | <0.1 | <0.2 |
| Calcium Carbonate - <10 20-30 <10 10-20 1317-65-3 Magnesite (total inhalable dust) (respirable dust) 5-10 <5 | Flux coating | Cellulose E6010, | E6012, | Hydrogen E7016, | Iron Powder | Iron Powder | Cas No. |
| (total inhalable dust) 5-10 <5 | | - | <10 | 20-30 | <10 | 10-20 | 1317-65-3 |
| (total inhalable dust) 25-60 <15 | (total inhalable dust) | 5-10 | <5 | - | - | - | 546-93-0 |
| Inorganic Fluorides (as F) | (total inhalable dust) | 25-60 | <15 | - | - | - | 9004-34-6 |
| Iron powder | Iron Oxides (as Fe) | <10 | <10 | <10 | <10 | | 1309-37-6 |
| Manganese and its Inorganic compounds (as Mn) 5-15 5-15 <15 <15 <10 7439-96-5 and others Rutile/Titanium Dioxide (total inhalable dust) (respirable dust) 10-35 15-60 <10 | | - | <10 | 10-30 | <10 | 5-15 | 16984-48-8 |
| Inorganic compounds (as Mn) | Iron powder | = | <10 | 10-35 | 10-60 | 10-60 | 7439-89-6 |
| (total inhalable dust) 10-35 15-60 <10 | Inorganic compounds | 5-15 | 5-15 | <15 | <15 | <10 | |
| Alloys, (as Si) Silicate Binders <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <5 <12001-26-2 (total inhalable dust) (respirable dust) Quartz/Silica Respirable crystalline <10 <15 <5 <5 <5 <5 <5 <1332-58-7 <5 <5 <5 <1332-58-7 | (total inhalable dust) | | 15-60 | <10 | 10-30 | <10 | 13463-67-7 |
| Mica <5 <20 <5 <5 <5 12001-26-2 (total inhalable dust) (respirable dust) - </td <td></td> <td>-</td> <td>-</td> <td><5</td> <td><5</td> <td><5</td> <td>7440-21-3</td> | | - | - | <5 | <5 | <5 | 7440-21-3 |
| (total inhalable dust) (respirable dust) Quartz/Silica Respirable crystalline <10 | Silicate Binders | <5 | <5 | <5 | <5 | <5 | 1344-09-8 |
| Respirable crystalline <10 | (total inhalable dust) | <5 | <20 | <5 | <5 | <5 | 12001-26-2 |
| | | <10 | <15 | 5-60 | <10 | <5 | 14808-60-7 |
| Other Mineral Silicates 5-30 5-30 5-10 5-30 5-10 1332-58-7 | Kaolin (respirable dus | t) - | <20 | = | <5 | <5 | 1332-58-7 |
| | Other Mineral Silicates | s 5-30 | 5-30 | 5-10 | 5-30 | 5-10 | 1332-58-7 |



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Section 4. FIRST AND MEASURES

4.1 Description of first aid measures

Inhalation IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position

comfortable for breathing. Call a physician if symptoms occur.

Skin contact Burns should be treated by a doctor.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Burns from radiation, see doctor.

Ingestion Contact a doctor if more than an insignificant amount has been swallowed.

4.2 Most important symptoms and effects, both acute and delayed

Inhalation Inhalation of vapours may cause irritation of the respiratory system in very susceptible

persons.

4.3 Indication of any immediate medical attention and special treatment needed

Not available

Section 5. FIRE-FIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Carbon dioxide (CO2), powder or diffuse jet of water. In case of major fire: Extinguish fire

with diffuse jet of water or foam.

5.2 Special hazards arising from the substance or mixture

Not available

5.3 Advice for fire fighters

Special protective equipment for No specific measures required for these electrodes prior to gouging.

fire fighters Gouging should not be carried out in the presence of flammable materials, vapours, tanks, cisterns and pipes and other containers which have held flammable substances unless

these have been checked and certified safe.

During a fire, irritating/toxic smoke and fumes may be generated. Do not enter fire area without proper protection. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full facepiece. Shield personnel to protect from venting, rupturing or bursting cans. Move containers from fire area if it can be done without risk. Water

spray may be useful in cooling equipment and cans exposed to heat and flame.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Section 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

General ventilation and local fume extraction must be adequate to keep fume concentrations within safe limits. Use respiratory equipment when welding in a confined space. Wear protective clothing and eye protection appropriate to arc welding. Skin contact should be avoided to prevent possible allergic reactions.

6.2 Environmental precautions

Try to prevent the material from entering drains or water courses.

6.3 Methods and material for containment and cleaning up

Not applicable

6.4 Reference to other sections

Personal protection see section 8 and for disposal see section 13. Environmental precautions, paragraph 12. See also section 7 Precautions for safe handling.

Section 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

| Preventive handling precautions | Ensure adequate ventilation for the welder and others. Use respiratory equipment when |
|---------------------------------|---|
| | welding in a confined space. Wear protective clothing and eye protection appropriate to arc |
| | welding. Remove all flammable materials and liquids before welding. |
| General hygiene | Wash hands before breaks and immediately after handling the product. |

7.2 Conditions for safe storage, including any incompatibilities

Store welding consumables inside a room without humidity. Do not store welding consumables directly on the ground or beside walls. Store away from chemical substances like acids which could cause chemical reactions.

7.3 Specific end use(s)

Welding process.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Section 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

8.1 Control parameters

| Welding fume component | CAS № | TLV- TWA | TLV-STEL | OTHER |
|--|------------|--|----------|---|
| Total welding fume (particulate) | | | | |
| Iron oxide fume (as Fe) | 1309-37-1 | 5 mg/m³ Respirable particulate mass | N/Av | N/Av |
| Manganese and its inorganic compounds (as Mn) | 7439-96-5 | 0.2 mg/m ³ | N/Av | N/Av |
| Silica, amorphous (total inhalable particles) (respirable particles) | N/Av | N/Av | N/Av | 10 mg/m ³ 3 mg/m ³ |
| Magnesium oxide (as Mg) (total inhalable dust) (fume and respirable dust) | 1309-48-4 | 10 mg/m ³ (Inhalable fraction) | N/Av | N/Av |
| Titanium dioxide (total inhalable dust) (respirable dust) | 13463-67-7 | 10 mg/m³ | N/Av | N/Av |
| Calcium Oxide | 1305-78-8 | 2 mg/m³ | N/Av | N/Av |
| Calcium Silicate (total inhalable dust) (respirable dust) | 1344-95-2 | 10 mg/m³ | N/Av | N/Av |
| Fluoride, inorganic (as F) | 16984-48-8 | N/Av | N/Av | N/Av |
| Nitrogen dioxide (NO ₂) | 10102-44-0 | 0.2 ppm | N/Av | N/Av |
| Ozone (O ₃) | 10028-15-6 | * | N/Av | N/Av |
| Nitrogen monoxide (NO) | 10102-43-9 | 25 ppm | N/Av | N/Av |

8.2 Exposure controls

Environmental Exposure Control – Refer to Section 6 of this SDS

| Technical precaution measures | General ventilation and local fume extraction must be adequate to keep fume |
|-------------------------------|--|
| | concentrations within safe limits. |
| Eye / face protection | Wear eye protection appropriate for welding. |
| Safety gloves | Skin contact should be avoided to prevent possible allergic reactions. |
| Other skin protection | Wear body protection which helps to prevent injury from radiation, sparks and electric |
| | shock. |
| Respiratory protection | Use respiratory equipment when welding in a confined space. Wear protective clothing |
| | and eye protection appropriate to arc welding. |



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Section 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance, colour Grey

Appearance, physical state Rod

Auto-ignition temperature Not applicable

Auto-flammability Not auto-flammable

Decomposition temperature Not applicable

Evaporation rate Not applicable

Explosive properties Not explosive

Flammability (solid gas) Not applicable

Flash point Not applicable

Form Metal wire with flux coating

Initial boiling point and boiling Not applicable

range

Melting point / Freezing point Not available

Odourless

Odour threshold Not available

Oxidising properties Not available

Partition coefficient: n-octanol / Not applicable

water

pH value Not applicable

Relative density Not applicable

Solubility Not available

Solubility in water Insoluble

Upper / lower flammability or Not applicable

explosive limits

Vapour density Not applicable

Vapour pressure Not applicable

Viscosity Not applicable

9.2 Other information

Not applicable

Other

Density 7.98g/cm³



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Section 10. STABILITY AND REACTIVITY

10.1 Reactivity

Not available

10.2 Chemical stability

Stable under the recommended storage and handling conditions prescribed. Hazardous polymerization will not occur. Incompatible materials and conditions to avoid are usually

related to welding.

10.3 Possibility of hazardous reactions

Not available

10.4 Conditions to avoid

None under normal conditions

10.5 Incompatible materials

Not available

10.6 Hazardous decomposition products

Welding fumes and gases. Additional fume may arise from coatings and contaminants on the base material. Hazardous combustion products - Carbon oxides and other irritating/toxic fumes and smoke.

| Welding fume component | № CAS | Classification (67/548EEC) | CLP (1272/20 | 08) | Concentration of classified fume components |
|--------------------------------|------------|---|-------------------------------------|----------------------|---|
| Aluminium oxide (Al) | 1344-28-1 | - | - | - | 1.8 to 1.2 |
| Barium (Ba) | 7440-39-3 | - | - | - | ≤0.1 |
| Bismuth oxide (Bi) | 12640-40-3 | - | - | - | ≤0.1 |
| Calcium (Ca) | 1305-78-8 | - | - | - | 0.1 to 11.6 |
| Cobalt oxide (Co) | 1307-96-6 | R22: Harmful if swallowed R43: May cause sensitisation by contact | Acute tox 4 (oral) Skin sens. 1 | H302 H317 | ≤0.1 |
| Chromium III compounds (as Cr) | 24613-89-6 | R45: May cause cancer R35: Causes severe burns R43: May cause sensitisation by skin contact | Carc. 1B Skin Corr. 1A Skin Sens. 1 | H350 H314 H317 | ≤0.1 |
| Copper oxide (Cu) | 1317-38-0 | - | - | - | ≤0.1 |
| Iron oxide (Fe) | 1332-37-2 | - | - | - | 11.9 to 54.9 |
| Potassium (K) | 7440-09-7 | R34: Causes burns | Skin Corr. 1B | H314 | 0.6 to 23.8 |
| Lithium (Li) | 7439-93-2 | R34: Causes burns | Skin Corr. 1B | H314 | 0.1 to 0.8 |



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

| | I | | | 1 | |
|-----------------------|------------|--|--|----------------------|-------------|
| Magnesium oxide (Mg) | 1309-48-4 | - | - | - | 0.1 to 5.3 |
| Manganese (Mn) | 7439-96-5 | - | - | - | 0.7 to 8.2 |
| Molybdenum (Mo) | 7439-98-7 | Molybdenum trioxide R36/37: Irritating to eyes and respiratory system R40: Limited evidence of carcinogenic effect | Molybdenum trioxide Carc. 2 Eye Irrit. 2 STOT SE 3 | H351 H319 H335 | ≤0.1 |
| Sodium (Na) | 7440-23-5 | R34: Causes burns | Skin Corr. 1B | H314 | 0.5 to 8.7 |
| Nickel (Ni) | 7440-02-0 | R40: Limited evidence of carcinogenic effect R43: May cause sensitisation by skin contact R48/23: Toxic danger of serious damage to health by prolonged exposure through inhalation R52/53: Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment | Carc. 2 Skin sens 1 STOT RE 1 | H351 H317 H372 | 0.1 to 0.2 |
| Lead (Pb) | 7439-92-1 | - | - | - | 0.1 to 1.8 |
| Silicon (Si) | 7440-21-3 | - | - | - | 2.1 to 16.3 |
| Titanium dioxide (Ti) | 13463-67-7 | - | - | - | 0.1 to 3.2 |
| Vanadium (V) | 7440-62-2 | - | - | - | ≤0.1 |
| Zinc (Zn) | 7440-66-6 | - | - | - | 0.1 to 3.5 |
| Fluoride (F-) | 16984-48-8 | - | - | - | 0.1 to 21.4 |

Final fume classification

| Classification | H phrase | Text |
|---|----------|---|
| Skin corrosion/irritation: Category 1B | H314 | Causes severe skin burns and eye damage |
| Carcinogenicity: Category 1B | H350 | May cause cancer |

The classification information above relates to the fume during use

| Fume analysis: wt % | Fume analysis: wt % |
|---------------------|---------------------|
| Al 0.1 to 1.2 | Ni 0.1 to 0.2 |
| Ca 0.1 to 11.6 | Pb 0.1 to 1.8 |
| Fe 11.9 to 54.9 | Si 2.1 to 16.3 |



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

| K | 0.6 to 23.8 | Ti 0.1 to 3.2 |
|----|-------------|----------------|
| Li | 0.1 to 0.8 | Zn 0.1 to 3.5 |
| Mg | 0.1 to 5.3 | F- 0.1 to 21.4 |
| Na | 0.5 to 8.7 | |

Section 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Conditions to avoid: none in the form supplied

When welding, fumes and gases generated can be dangerous to health.

Acute toxiciy Excessive exposures may affect human health, as follows: Aspiration may cause pulmonary

oedema and pneumonitis Short-term overexposure can cause dizziness, nausea and irritation

of the nose, throat or eyes.

Irritation Not available

Corrosive effects Not available

Sensitisation May cause sensitisation by skin contact

Mutagenicity Not available

Carcinogenicity Welding fumes are possibly carcinogenic to humans

Repeated dose toxicity
Reproductive toxicity
Not available
Synergistic materials
Not available

Section 12. ECOLOGICAL INFORMATION

12.1 Toxicity

The welding process can effect the environment if fume is released directly into the atmosphere. Residues from welding consumables could degrade and accumulate into soils and ground water.

12.2 Persistence and degradability

Not available

12.3 Bio accumulative potential

Not available

12.4 Mobility in Soil

Not available

12.5 Results of PBT and vPvB assessment



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Not available

12.6 Other adverse effects

Not available

Section 13. DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Disposal considerations Dispose of any product, residue or packing material according to national and local

regulations. Spent fume extraction filters shall be disposed of as dangerous waste.

Other

Waste code

Packaging and rod scrap should be disposed of as general waste or recycled. No special precautions are required for this product. Fume collected from extraction units should be disposed of in accordance with local regulations (including Provincial and Federal Paradations). Only a talk and the state of t

Regulations). Collect all spillage.

Section 14. TRANSPORT INFORMATION

14.1 UN number

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not applicable

14.6 Special precautions for user

Not applicable

14.7 Transport in bulk

Not applicable

Other



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

Dangerous goods

No special requirements are necessary in transporting these products.

Transportation of Dangerous Goods Regulations (TDGR):

TDG Classification: NOT REGULATED

Special case: N/Ap

Section 15. REGUATORY INFORMATION

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture.

EU reguations
National regulations

EU reguations Refer to national Regulations.

WHMIS Label Information: **WARNING.** Do not remove or cover this Warning. Protect yourself and others. Read and understand this information. Electric shock can kill. Keep your head out of the fume. Arc rays and fume can affect others in your workplace. Comply with your employer's safety practices and procedures: protect others.

Safety data sheet available on request from www.messer-ca.com.

WHMIS information: Product is regulated according to the Controlled Product Regulations (CPR) in Canada. This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and this SDS contains all the information required by the CPR.

WHMIS classification: D2A - Toxic Material with other effects.

15.2 Chemical safety assessment

Not available

Section 16. OTHER INFORMATION

References to key literature and data sources

The customer should provide this Safety Data Sheet to any person involved in the materials use or further distribution. The Messer World requests the users (or distributors) of this product to read this Safety Data Sheet carefully before usage.

Prepared by Messer Canada Inc.

References

Safety Data Sheets from manufacturer/supplier.

Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2014.

Phrase meaning

Abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstract Service

IARC International Agency for Research on Cancer

LC Lethal concentration LD Lethal Dosage N/Ap Not applicable N/Av Not available

NIOSH National Institute for Occupational Safety and Health

STEL Short-term Exposure Limit TLV Threshold Limit Value TWA Time Weighted Average

WHMIS Workplace Hazardous Materials Information System

Other

Manufacturer's notes

The information contained in this Safety Data Sheet relates only to the specific materials designated and may not be valid for such material used in combination with any other material or in any process.

Information is given in good faith and is based on the latest information available to The Messer World and is, to the best of The Messer Canada's knowledge and belief, accurate and reliable at the time of preparation. However, no representation, warranty or guarantee is made as to the accuracy, reliability or completeness of the information, and Messer World assumes no responsibility and disclaims any liability incurred in using this information.



Version number: 1

Replaces SDS: 2009-11-23

Issued: 2020-03-05

The product is supplied on the condition that the user accepts the responsibility to satisfy himself as to the suitability and completeness of such information for his own particular use. Freedom from patent rights must not be assumed.

Read this Safety Data Sheet carefully and become aware of hazards implied and the safety information.

End of document